

RECEIVED
CENTRAL FAX CENTER

Appl. No. 10/065,523
Reply to Final Office action of September 12, 2005

DEC 12 2005

23. (Original) The apparatus of claim 22, further including a mechanism for moving the mounting automatically based on the extension of the at least two arms, whereby pivoting of the arms in at least one direction is limited by the amount of extension of the at least two arms.

24. (Original) The apparatus of claim 21, wherein the mechanism for pivoting includes a hydraulic cylinder.

25. (Previously Presented) The apparatus of claim 17 further including a mounting for transporting oilfield apparatus, the mounting being disposed between the at least two telescoping load bearing arms and moving with the mast assembly as it pivots between a stowed position and at least an upright position.

26. (Previously Presented) The apparatus of claim 17, further including a cross member coupled between ends of the at least two telescoping load bearing arms, the cross member including a latch to which oilfield apparatus may be attached for lifting by the mast assembly.

27. (Currently Amended) The apparatus of claim 26, further comprising a coiled tubing mounting and a blowout preventer mounting disposed between the at least two telescoping load bearing arms, wherein the cross member including a trolley for moving laterally the latch.

28. (Previously Presented) The apparatus of claim 27, wherein the blowout prevent mounting slides laterally between the at least two telescoping load bearing arms.

29. (Previously Presented) Apparatus for hoisting oilfield apparatus over a well head comprising a mast assembly with at least two telescoping load bearing arms coupled pivotably coupled to a base, the plurality of arms each comprising a plurality of synchronously operable, coaxially aligned, load bearing telescoping segments for extending and retracting in

Incompletely printed out 01/10

Appl. No. 10/065,523

Reply to Final Office action of September 12, 2005

unison, the apparatus further including a mechanism coupled between the mast assembly and the mounting for pivoting the at least two telescoping arms, the mechanism for pivoting being limited in extension and coupled at one end to a moveable mounting, the movable mounting responsive to extension of the at least two telescoping arms.

30. (Canceled)

31. (Canceled)

32. (Previously Presented) The apparatus of claim 29, further including a cross member coupled between ends of the at least two telescoping load bearing arms, the cross member including a latching mechanism to which oilfield apparatus may be attached for lifting by the mast assembly.

33. (Previously Presented) The apparatus of claim 29, further including a mounting for transporting oilfield apparatus, the mounting being disposed between the at least two telescoping load bearing arms and moving with the mast assembly as it pivots between a stowed position and at least an upright position, wherein the mounting includes a coiled tubing injector support and a blow out preventer support.

34. (Previously Presented) The apparatus of claim 33, further including a cross member coupled between ends of the at least two telescoping load bearing arms, the cross member including a latch to which oilfield apparatus may be attached for lifting by the mast assembly and a trolley for moving laterally the latch.

35. (Previously Presented) The apparatus of claim 33, wherein the blowout preventer support slides laterally between the at least two telescoping load bearing arms.

36. - 38. (Cancelled)

43. (Currently Amended) The apparatus of claim 40, wherein the support base member is mounted to a vehicle.

44. (Currently Amended) The apparatus of claim 40, wherein the plurality of synchronously operable, coaxially aligned, telescoping nesting segments comprise roller bearings to reduce friction therebetween when raising and lowering the oilfield apparatus.

BEST AVAILABLE COPY